

SP12-5 (12V 5Ah)

Features


- ✔ 5 years design life (25°C)
- ✔ Special exhaust structure and sealing technology, safe and reliable, flexible installation, convenient maintenance
- ✔ PbCaSn alloy for plate grids: less gassing, less self-discharging
- ✔ High quality AGM separator: extend cycle life and prevent micro short circuit
- ✔ High purity raw material: ensure low self discharge rate



Applications

- ✓ All purpose
- ✓ Uninterruptable Power Supply (UPS)
- ✓ Electric Power System (EPS)
- ✓ Emergency backup power supply
- ✓ Alarm and security system
- ✓ Communication power supply
- ✓ DC power supply
- ✓ Auto control system
- ✓ Solar Power Systems
- ✓ Wheel chair and Mobility Scooters

LAYOUT



Standards

- ✔ Compliance with IEC 60896 standards, EU Battery Directive
- ✔ UL, CE Certified
- ✔ Manufactured at Supreme Power Systems, ISO Certified Production facilities® IATF 16949, ISO 45001, ISO 9001 and ISO 14001 certified production facilities

SPECIFICATIONS

Rated Voltage	12V	
Nominal Capacity	5.0Ah	(C ₆₄ , 1.75V/cell)
Dimensions	Length	151±2mm (5.94 inches)
	Width	53±1mm (2.09 inches)
	Container height	93±1mm (3.66 inches)
	Total height	99±1mm (3.90 inches)
Approx. weight	1.73 Kg (3.81 lbs)	
Terminal	T1/T2	
	ABS	
Rated capacity (25°C)	4.50 Ah	(20hr,0.250A,1.75V/cell)
	4.19 Ah	(10hr,0.473A,1.75V/cell)
	3.83 Ah	(5hr,0.861A,1.75V/cell)
	3.39 Ah	(3hr,1.28A,1.75V/cell)
	2.66 Ah	(1hr,3.29A,1.60V/cell)
Max. discharge current	75A (5s)	
Internal resistance (25°C)	Approx 35mΩ	
Operating temp. range	Discharge	-15~50°C (5~122°F)
	Charge	-20~40°C (-4~104°F)
	Storage	-15~40°C (5~104°F)
Nominal operating temp. range	25±3°C (77±5°F)	
Cycle Use	Initial Charging Current less than 1.5A. Voltage 14.4V~15.0V at 25°C(77°F)Temp. Coefficient -30mV/°C	
Standby Use	Initial Charging Current less than 1.5A. Voltage 13.5V~13.8V at 25°C(77°F)Temp. Coefficient -20mV/°C	
Effect of temp. to Capacity	40°C (104°F)	103%
	25°C (77°F)	100%
	0°C (32°F)	86%
Self discharge	SP series batteries may be stored for up to 6 months at 25°C(77°F) and then a freshening charge is required. For higher temperatures the time interval will be shorter.	


Constant Current Discharge (Amperes) at 25°C (77°F)

F.V/Time	5min	10min	15min	20min	30min	45min	1h	1.5h	2h	3h	4h	5h	6h	8h	10h	2h
1.85V/cell	16.4	10.9	8.33	6.75	4.97	3.63	2.97	2.18	1.71	1.24	0.984	0.838	0.717	0.565	0.462	0.244
1.80V/cell	17.6	11.6	8.74	7.02	5.12	3.73	3.05	2.22	1.74	1.26	1.00	0.850	0.729	0.573	0.468	0.247
1.75V/cell	18.5	12.1	9.03	5.68	5.25	3.81	3.11	2.26	1.77	1.28	1.01	0.861	0.737	0.579	0.473	0.250
1.70V/cell	19.4	12.5	9.33	7.42	5.39	3.89	3.17	2.30	1.80	1.29	1.03	0.872	0.746	0.585	0.478	0.252
1.67V/cell	20.1	12.9	9.56	7.57	5.48	3.96	3.21	2.33	1.82	1.31	1.04	0.880	0.752	0.590	0.481	0.254
1.60V/cell	21.3	13.4	9.89	7.80	5.63	4.06	3.29	2.38	1.86	1.33	1.05	0.894	0.763	0.598	0.487	0.257


Constant Power Discharge (Watts/cell) at 25°C (77°F)

F.V/Time	5min	10min	15min	20min	30min	45min	1h	1.5h	2h	3h	4h	5h	6h	8h	10h	2h
1.85V/cell	30.9	20.8	15.9	13.0	9.60	7.04	5.78	4.25	3.35	2.43	1.94	1.65	1.42	1.12	0.918	0.489
1.80V/cell	33.0	21.9	16.6	13.4	9.85	7.21	5.91	4.33	3.41	2.46	1.96	1.68	1.44	1.14	0.930	0.495
1.75V/cell	34.3	22.6	17.1	13.7	10.1	7.33	6.00	4.40	3.46	2.50	1.99	1.69	1.45	1.15	0.938	0.500
1.70V/cell	35.6	23.4	17.5	14.1	10.3	7.47	6.10	4.46	3.50	2.53	2.01	1.72	1.47	1.16	0.947	0.504
1.67V/cell	36.5	23.9	17.9	14.3	10.4	7.57	6.18	4.51	3.53	2.55	2.03	1.73	1.48	1.17	0.954	0.508
1.60V/cell	38.0	24.6	18.4	14.7	10.7	7.71	6.29	4.58	3.59	2.59	2.06	1.75	1.50	1.18	0.965	0.514


Discharge Characteristics



Float Charging Characteristics



Temperature Effects in relation to Battery Capacity



Float Service Life

